


Electr. Digital Universal Bevel Protractor Set

- with data output
- with 3 blades (150 / 200 / 300 mm), 90° square and angle stop
- stainless steel, hardened and fine ground
- rugged ABS-plastic housing, multifunctional display
- with fine adjustment for easy adjustment and fixing device for the blade
- large LCD display with clear reading
- two display lines, resolution in 1. line with 0.005° and in 2. line with min. 10"
- preset to 360° / 180° / 90°, two measuring directions selectable
- On/Off button, mode-button, set-button, zero setting at any position
- automatic switch off after approx. 5 min
- operation temperature 0 °C ~ +40 °C, storage temperature -10 °C ~ +60 °C
- incl. 1x 3 V battery (type CR2032, art.-no.: 90112), with operation manual

Option

- data transfer via cable, art.-no. 2420192, see page 334



90° angled adjustment



angle stop



ART N°	length of blade mm				
320100	150 / 200 / 300	360° / 2x 180° / 4x 90°	0.005° / 10"	5"	on request

Universal Bevel Protractor Set

- set with 3 blades in different length

- stainless, hardened and fine ground
- scales matt chrome finish
- parallaxfree reading by vernier, with large magnifying lens
- with fine adjustment
- incl. 90° angled adjustment (art.-no.: 321275) and angle stop (art.-no.: 321276)

Option


- wooden case (art.-no.: 3299020)



90° angled adjustment



angle stop



ART N°	length of blades mm		angle graduation	
321220	150 / 200 / 300 mm	4 x 90°	1/12° = 5'	on request

Protractor (Skew Measurer)

- for standard mechanical engineering

- special steel, in chromed finish
- scale in matt chrome finish
- with adjustable blade, with fixing screw

Accessories can be found on page 201



ART N°	length of blades mm	arc-ø mm	angle graduation
320571	150	100	10 – 170°
320572	300	150	10 – 170°
320573	400	200	10 – 170°
320574	500	250	10 – 170°