





Electr. Digital Moisture Meter

- for measurements of wood moisture, paper, building materials, etc.
- with 4 contact pins
- rugged, polyamide housing material
- large LCD display with clear reading
- On/Off button, data hold button
- autom. power off, battery indicator
- setting the upper limit of the moisture ratio
- storage temperature -10 °C ~ +60 °C, operation temperature 0 °C ~ +40 °C, rel. humidity < 70 % RH
- incl. 1x 9 V battery (type 6LR61, art.-no.: 90006)
- with operation manual







ART No	 wood	 1.0 %	 ±1.0 % Rh+0.5	 mm 129 x 63 x 32
641006	5 % – 40 %			

Electr. Digital Moisture Meter

NEW

- for measurement of building materials, concrete, wood, etc.
- robust, ABS plastic housing
- large LCD display, 3 digits, with clear reading, digit height 15 mm
- On / Off key, data hold function, min / max key, measurement in digits
- depth of penetration about 20 – 40 mm
- low battery indication, backlight switchable
- storage temperature 0 °C ~ 50 °C, rel. Humidity < 80 % RH
- incl. 1x 9 V battery (type 6LR61, art.-no.: 90006), with operation manual










ART No	 capacity device digits	 digit	 digit ±1	 mm 180 x 45 x 35
641009	0 – 100	1		

Electr. Digital Moisture Meter

- for measurements of wood moisture, paper, carton, building material, grain, etc.
- with insulating peel
- measurement via 2 external contact pins
- rugged, polyamide housing material
- large LCD display with clear reading
- On/Off button, data hold button, button for wood density selection
- button for selection of moisture measurement / temperature measurement (in °C or °F)
- battery indicator, with backlight
- setting the upper limit of moisture ratio, rel. humidity < 70 % RH
- storage temperature -10 °C ~ +60 °C, operation temperature -10 °C ~ +40 °C
- incl. 4x 1.5 V battery (type AA, art.-no.: 90003)
- with operation manual



ART No	 wood	 0.5 %	 ±1.0 % Rh +0.5	 temperature -10 °C – 60 °C	 temperature 1 °C / 2 °F	 ±2 °C / ±4 °F	 housing 174 x 38 x 73
641008	2 % – 70 %						